




SB3 1200 x 1000 x 790 mm / 610 l



Art.-Nr.: 81941891

Technical data			
Dimensions L x W x H (mm)	1200 X 1000 X 790		
Weight(kg)	40.5 kg		
Volume (I)	610		
Material	PE		
Load capacity (kg)	Stacking Load 5000 kg	Holding Capacity 700 kg	by Dynamic Load

Characteristics

Colour: light grey

Manufactured in one piece

Runners: 9 feet Stackable

Temperature stability: -30 $^{\circ}\text{C}$ to +40 $^{\circ}\text{C},$ briefly up to +90 $^{\circ}\text{C}$

 $Resistant \, to \, most \, chemicals \, and \, cleaning \, agents \,$

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048

Options

Drain port 3 Runners


Fully perforated walls / base

Loading quantities (Pcs / Approximate amount)

Container	Container 20': 30 Container 40': –	Container 40' High Cube: 84 Conventional trailer 45' high cube container: 104		
Truck	MEGA-Trailer: 130	Jumbo: 140-150		

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Stacking Load: at a room temperature of approx. 20°C. Dynamic Load: on a forklift with an evenly distributed load at a room temperature of approx. 20°C.