






HB3

1200 × 1000 × 790 mm / 620 l



Art.-Nr.: 83421800

Technical data			
Dimensions L x W x H (mm)	1200 x 1000 x 790		
Weight (kg)	44.0 kg		
Volume (l)	620 l		
Material	PE		
Load capacity (kg)	kg  Stacking Load 5000 kg	kg  Holding Capacity 900 kg	kg  Dynamic Load 1900
Characteristics		Options	
Colour: light grey Runners: 3, welded Stackable Temperature stability: -30 °C to +40 °C, briefly up to +90 °C Resistant to most chemicals and cleaning agents Food-safe. HACCP compliant Container is based on DIN EN 13626 and DIN EN ISO 12048		Reinforcement profiles Lid Drain port	
Loading quantities (Pcs / Approximate amount)			
 Container	Container 20': – Container 40': –	Container 40' High Cube: – Conventional trailer 45' high cube container: 104	
 Truck	MEGA-Trailer: 104		Jumbo: 112-120
Labelling			
Customised printing and numbering available on request depending on quantity. Position upon consultation.			



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Stacking Load:** With a maximum stacking height of 6 boxes (5 on 1 stacking) and evenly distributed load at approx. 20 °C.
Dynamic Load: On a forklift with an evenly distributed load at a room temperature of approx. 20 °C.