





D2 800 x 600 mm





Art.-Nr.: 83512201

Technical Data*1		
Dimensions L x W x H (mm)	800 x 600 x 160 mm	
Weight(kg)	8,5 kg	
Material*2	PP	
Load capacity (kg)* ³	Static 2000 kg	Dynamic 500 kg
Characteristics		Options
Colour: black Runners: 3, unwelded Rims: 7 mm Temperature stability: -18 °C to +40 °C, briefly up	to +90 °C	Rimoptions Antislip Lid
Loading quantities (Pcs / Approximate a	nount)	
Container	Container 20': 384 Container 40': 780	Container 40' High Cube: 880 Conventional trailer 45' high cube container: -
Truck	MEGA-Trailer: 1224	Jumbo: 1368

Labelling

 $Customised\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.
 Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 200 h at a room temperature of approx. 20 °C.