








CS1 ESD

1200 x 800 mm



Art.-Nr.: 83192208

Technical Data**

Dimensions L x W x H (mm)	1200 x 800 x 146 mm		
Weight (kg)	12.5 kg		
Material*2	PE, ESD		
Load capacity (kg)*3	 Static 5000 kg	 Dynamic 1000 kg	 In Racking System 400 kg

Characteristics	Options
Colour: black Runners: 3, unwelded Rims: 22 mm outside Temperature stability: -30°C to +40°C, briefly up to +90°C ESD pallet Surface resistance of $\geq 1 \times 10^{10}$ E4 Ohm to $< 1 \times 10^{11}$ Ohm	Rimoptions Welded runner Transponder (RFID) Lid

Loading quantities (Pcs / Approximate amount)

	Container	Truck
Container 20':	215	
Container 40':	440	
Container 40' High Cube:	465	
Conventional trailer 45' high cube container:		
MEGA-Trailer:		627
Jumbo:		722

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
 *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
 *3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20°C.
Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20°C.
In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.