











CS1 ESD

1200 x 800 mm



Art.-Nr.: 83192208

Technical data			
Dimensions L x W x H (mm)	1200 x 800 x 146		
Weight(kg)	12.5 kg		
Material	PE, ESD		
Load capacity (kg)	 Static 5000 kg	 Dynamic 1000	 In Racking System 400
Characteristics		Options	
Colour: black		Rimoptions	
Runners: 3, unwelded		Welded runner	
Rims: 22 mmoutside		Transponder (RFID)	
Temperature stability: -30 °C to +40 °C, briefly up to +90 °C			
ESD pallet			
Surface resistance of ≥ 1 x 10 E4 Ohmto < 1 x 10 E11 Ohm			
Loading quantities (Pcs / Approximate amount)			
 Container	Container 20': 215 Container 40': 440	Container 40' High Cube: 465 Conventional trailer 45' high cube container: 528	
 Truck	MEGA-Trailer: 627	Jumbo: 722	
Labelling			
Customised printing and numbering available on request depending on quantity. Position upon consultation.			



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.