




KUBO

1240 x 835 x 973 mm / 610 l




Art.-Nr.: 82601811

Technical Data*1			
External Dimensions L x W x H (mm)	1240 x 835 x 973	Internal Dimensions L x W x H (mm)	1133 x 726 x 832
Weight (kg)	51.5 kg	Volume (l)	610 l
Material*2	PE		

Load capacity (kg)*3	 Extra Load 3000kg	 Holding Capacity 1000kg	 Dynamic Load 2100kg
----------------------	-----------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------

Characteristics	Options
Colour: light grey Body injection-moulded in one piece Runners: 4 feet Stackable Temperature stability: -30 °C to +40 °C, briefly up to +90 °C Resistant to most chemicals and cleaning agents External dimensions based on UIC 435-3 External dimensions compatible with the metal grid box (Gitterbox) enable use in existing systems.	Documents holder Transponder (RFID)

Loading quantities (Pcs / Approximate amount)

 Truck	MEGA-Trailer: 96	Jumbo: 108
-------------------------------------------------------------------------------------------------	-------------------------	-------------------

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
 *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
 *3 Extra load with a holding capacity of 1000 kg at room temperature. Dynamic load on a forklift with an evenly distributed load at a room temperature.