










CanPal® German

1265 X 1180 X 133



Art.-Nr.: 83010800

Technical Data*1		
Dimensions L x W x H (mm)	1265 x 1180 x 133 mm	
Weight (kg)	22.6 kg	
Material*2	PP	
Load capacity (kg)*3	 Static 10000 kg	 Dynamic 1250 kg
		 In Racking System
Characteristics		Options
Colour: light grey Runners: 5, unwelded With spacers Temperature stability: -18 °C to +40 °C, briefly up to +90 °C		Palgrip® anti-slip clips on the top of the deck Transponder (RFID) Palgrip® anti-slip clips on the underside of the deck
Loading quantities (Pcs / Approximate amount)		
 Container	Container 20': - Container 40': -	Container 40' High Cube: - Conventional trailer 45' high cube container: 380
 Truck	MEGA-Trailer: 440	Jumbo: 528
Labelling		
Customised printing and numbering available on request depending on quantity. Position upon consultation.		



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.
Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.