




Art.-Nr.: 81941998

SB3 UN 50H

50H/X/..../F/CRAEMER BVT 40513/2160/600



Technical Data*¹

External Dimensions (mm)	1200 x 1000 x 790 mm (with lid: 1218 x 1018 x 834 mm)	Internal Dimensions (mm)	1122 x 912 x 590 mm
Weight (kg)	51.5 kg	Volume (l)	610 l
Material* ²	PE		

Load capacity (kg)



Extra Load

1200kg

Characteristics



Holding Capacity

600kg



Dynamic Load

Options

Colour: light grey

Manufactured in one piece

Runners: 3, unwelded

With lid and 2 tensioning straps

Stackable

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C Transponder (RFID)

Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048


The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)


Loading quantities (Pcs / Approximate amount)

On request

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.





All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

SB3 UN 50H, 81941998, 02/2025, Nr.1