







SB 999l UN 4H2

4H2/Y473/S/--/NL/2139-250601



Art.-Nr.: 81941997

Technical Data*1			
External Dimensions (mm)	1600 x 1200 x 790 mm (with lid 1619 x 1219 x 862 mm)	Internal Dimensions (mm)	1520 x 1120 x 590 mm
Weight (kg)	73.5 kg	Volume (l)	999 l
Material*2	PE		
Load capacity (kg)	 Extra Load 1271kg	 Holding Capacity 473,3kg	 Dynamic Load



Characteristics	Options
Colour: light grey Runners: 4, unwelded Stackable Temperature stability: -30°C to +40°C, briefly up to +90°C Resistant to most chemicals and cleaning agents Food-safe. HACCP compliant Container is based on DIN EN 13626 and DIN EN ISO 12048 The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)	Transponder (RFID)

Loading quantities (Pcs / Approximate amount)

On request

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.