







# CanPal® German

1265 X 1180 X 133



Art.-Nr.: 83010801

Technical Data*1			
Dimensions L x W x H (mm)	1250 x 1180 x 133 mm		
Weight (kg)	22.6 kg		
Material*2	PP		
Load capacity (kg)*3	 <b>Static</b> 10000 kg	 <b>Dynamic</b> 1250 kg	 <b>In Racking System</b>
Characteristics		Options	
Colour: light grey Runners: 5, unwelded Temperature stability: -18 °C to +40 °C, briefly up to +90 °C		Palgrip® anti-slip clips on the top of the deck Transponder (RFID) Palgrip® anti-slip clips on the underside of the deck	
Loading quantities (Pcs / Approximate amount)			
 <b>Container</b>	Container 20': - Container 40': -	Container 40' High Cube: - Conventional trailer 45' high cube container: <b>380</b>	
 <b>Truck</b>	MEGA-Trailer: <b>440</b>	Jumbo: <b>528</b>	
Labelling			
Customised printing and numbering available on request depending on quantity. Position upon consultation.			



\*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

\*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

\*3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

**Dynamic load:** on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

**In racking system:** evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.