


# CR1

47.2" x 31.5"






Art.-Nr.: 83230801

Palgrip



## Technical Data\*1

Dimensions L x W x H	47.2 x 31.5 x 6.3" (1200 x 800 x 160 mm)		
Weight (lbs)	41.9 lbs		
Material*2	PE		
Load capacity (lbs)	 <b>Static</b> 16550 lbs	 <b>Dynamic</b> 3850 lbs	 <b>In Racking System</b> 3850 lbs



## Characteristics

Color: dark gray / blue  
 Runners: 3, unwelded  
 Reinforcement profiles: 3  
 Antislip: Palgrip® anti-slip strips on the top deck  
 Temperature stability: -22°F to +104°F, briefly up to +194°F

## Options

Transponder (RFID)  
 Lip options  
 Lid

## Loading quantities (Pcs / Approximate amount)

 <b>Container</b>	Container 20': <b>192</b>	Container 40' High Cube: <b>440</b>
	Container 40': <b>390</b>	Conventional trailer 45' high cube container: -
 <b>Truck</b>	MEGA-Trailer: <b>612</b>	Jumbo: <b>684</b>

## Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.



\*1 All technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration. All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.

\*2 Our service team is available to provide precise information about material compositions.

\*3 **Static load:** Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68°F.

**Dynamic load:** On a forklift with an evenly distributed load at a room temperature of approx. 68°F.

**In racking system:** Evenly distributed load (sacks) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68°F.