




**CR1**47.2" x 31.5"



Art.-Nr.: 83230800

Technical Data*1			
Dimensions L x W x H	47.2 x 31.5 x 6.3" (1200 x 800 x 160 mm)		
Weight(lbs)	35.3 lbs		
Materia *²	PE		
Load capacity (lbs)	Static 11000 lbs	Dynamic 2800 lbs	In Racking System 2200 lbs
Characteristics		Ontions	


Characteristics	options
Color: gray/blue	Transponder (RFID)
Runners: 3, unwelded	Reinforcement profiles
Antislip: Palgrip <sup>®</sup> anti-slip strips on the top deck Temperature stability: -22°F to +104°F briefly up to +194°F	Lid Lip options

## Loading quantities (Pcs / Approximate amount

Loading quantities (res / Approximate amount)				
Container	Container 20': <b>192</b> Container 40': <b>390</b>	Container 40' High Cube: <b>440</b> Conventional trailer 43' high cube container: -		
Truck	MEGA-Trailer: 612	Jumbo: <b>684</b>		

## Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.









- 1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- $^{*2} \quad \hbox{Our service team is pleased to be at your disposal if you require exact information about material compositions}.$
- \*3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68 °F.

  Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68 °F.

  In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68 °F.