




## **EURO H1**









Technical Data*1			
Dimensions L x W x H	47.2 × 31.5 × 6.3 " (1200 × 800 × 160 mm)		
Weight(lbs)	39.7 lbs		
Material* <sup>2</sup>	PE		
Load capacity (lbs)	Static 11000 lbs	Dynamic 2800 lbs	In Racking System 2200 lbs

Characteristics **Options** 

Lid Color: light gray

Runners: 3, welded Central box retainers: Yes

Lips: 0.3 "

Temperature stability: -22°F to +104°F, briefly up to +194°F

GS1 certified, Europe-wide exchangeability, with "GS label for tested safety", DIN 55423-5 and


55423-6 certification

## Loading quantities (Pcs / Approximate amount)

Container	Container 20': <b>192</b> Container 40': <b>390</b>	Container 40' High Cube: <b>440</b> Conventional trailer 45' high cube container: -
Truck	MEGA-Trailer: <b>594</b>	Jumbo: <b>684</b>

## Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.







- All technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration. All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.
- \*2 Our service team is available to provide precise information about material compositions.
- \*3 Static load: Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68 °F.

  Dynamic load: On a forklift with an evenly distributed load at a room temperature of approx. 68 °F.

  In racking system: Evenly distributed load (E2 boxes or Euro fish boxes) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68 °F.