








H1
47.2" x 31.5"



Art.-Nr.: 83100801

Technical Data*1			
Dimensions L x W x H	47.2 x 31.5 x 6.3 " (1200 x 800 x 160 mm)		
Weight (lbs)	39.7 lbs		
Material*2	PE		
Load capacity (lbs)	 Static 11000 lbs	 Dynamic 2800 lbs	 In Racking System 2200 lbs
Characteristics		Options	
Color: light gray Runners: 3, welded Lips: 0.3 " Temperature stability: -22°F to +104°F, briefly up to +194°F		Lid Transponder (RFID) Palgrip® anti-slip runners	
Loading quantities (Pcs / Approximate amount)			
 Container	Container 20': 192 Container 40': 390	Container 40' High Cube: 440 Conventional trailer 45' high cube container: -	
 Truck	MEGA-Trailer: 594	Jumbo: 684	
Labelling			
Customized printing and numbering available on request depending on quantity. Position upon consultation.			



- *1 All technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration. All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.
- *2 Our service team is available to provide precise information about material compositions.
- *3 **Static load:** Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68 °F.
Dynamic load: On a forklift with an evenly distributed load at a room temperature of approx. 68 °F.
In racking system: Evenly distributed load (E2 boxes or Euro fish boxes) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68 °F.