







TC1

47.2" X 31.5"





Art.-Nr.: 87065201

**Pal**<sup>grip</sup>

Technical Data*1				
Dimensions L x W x H	47.2 × 31.5 × 6.3 " (1200 × 800 × 160	47.2 X 31.5 X 6.3 " (1200 X 800 X 160 mm)		
Weight(lbs)	39.7 lbs			
Material* <sup>2</sup>	PE			
Load capacity (lbs)	Static 16550 lbs	Dynamic 2800 lbs	In Racking System 2200 lbs	
Characteristics		Options		
Color: black Runners: 3, unwelded Lips: 0.3"		Transponder (RFID) Reinforcement profiles Lip options		

Lid

## Temperature stability: -22°F to +104°F, briefly up to +194°F Loading quantities (Pcs / Approximate amount)

	,
Container	Containe

Container Container 201: **192** Container 401 High Cube: **440** Conventional trailer 451 high cube container:



MEGA-Trailer: 612

Jumbo: 684

## Labelling

 $Customized\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$ 









- \*1 All technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration.

  All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.
- \*2 Our service team is available to provide precise information about material compositions.
- \*3 Static load: Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68 °F.

  Dynamic load: On a forklift with an evenly distributed load at a room temperature of approx. 68 °F.

  In racking system: Evenly distributed load (sacks) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68 °F.