





D147.2" x 31.5"






Art.-Nr.: 83360231

Technical Data*1				
Dimensions L x W x H	47.2 x 31.5 x 5.9 " (1200 x 800 x 150 mm)			
Weight(lbs)	32 lbs			
Material* ²	PE			
Load capacity (lbs)	Static 11000 lbs	Dynamic 2800 lbs	In Racking System 2200 lbs	
Characteristics		Options		
Color: black Runners: 3, unwelded Reinforcement profiles: 3 Lips: 0.3 " Temperature stability: -22°F to +104°F, briefly up to +194°F		Transponder (RFID) Reinforcement profiles Lip options Antislip Lid		
Loading quantities (Pcs / Approximate amount)				
Container	Container 20': 215 Container 40': 440	Container40' High Cube: 46 Conventional trailer45' hig	Container 40' High Cube: 465 Conventional trailer 45' high cube container:-	
FL Truck	MEGA-Trailer: 646	Jumbo: 722		
Labelline				

Labelling

 $Customized\ printing\ and\ numbering\ available\ on\ request depending\ on\ quantity.\ Position\ upon\ consultation.$









- 1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68 °F.

 Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68 °F.

 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68°F.