







Non-Stop

1200 x 800 mm



Art.-Nr.: 83241725

Technical Data* ¹			
Dimensions L x W x H	47.2 x 31.5 x 6.9 " (1200 x 800 x 175 mm)		
Weight(lbs)	44.1 lbs		
Material* ²	PE		
Load capacity (lbs)	 Static 16550 lbs	 Dynamic 2200 lbs	 In Racking System
Characteristics		Options	
Color: red brown / black		Lid	
Runners: 3, welded			
Euro pallet with thermoformed top layer			
Temperature stability: -22°F to +104°F, briefly up to +194°F			
Loading quantities (Pcs / Approximate amount)			
 Container	Container 20': 170 Container 40': 330	Container 40' High Cube: 330 Conventional trailer 45' high cube container: -	
 Truck	MEGA-Trailer: 578	Jumbo: 612	
Labelling			
Customised printing and numbering available on request depending on quantity. Position upon consultation.			



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68°F.
Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68°F.
In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68°F.