





**H3** 






## Art.-Nr.: 83180801

Technical Data*1			
Dimensions L x W x H	47.2 x 39.4 x 6.3 (1200 x 1000 x 160 mm	1)	
Weight(lbs)	48.5 lbs		
Material*2	PE		
Load capacity (lbs)	Static 11000 lbs	Dynamic 2800 lbs	In Racking System 1850 lbs
Characteristics		Options	
Color: light gray Runners: 3, welded Lips: 0.3" Temperature stability: -22°F to +104°	F, briefly up to +194° F	Central box retainers Palgrip <sup>®</sup> anti-slip runners Lid	
Loading quantities (Pcs / Appro	oximate amount)		
Container	Container 20': <b>141</b>	Container 40' High Cube: <b>340</b>	

Container	Container 20': <b>141</b> Container 40': <b>300</b>	Container 40' High Cube: <b>340</b> Conventional trailer 45' high cube container: -
Truck	MEGA-Trailer: 468	Jumbo: <b>504-540</b>

## Labelling

 $Customized\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$ 









- all technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration.

  All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.
- \*2 Our service team is available to provide precise information about material compositions.
- \*3 Static load: Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68 °F.
  Dynamic load: On a forklift with an evenly distributed load at a room temperature of approx. 68 °F.
  In racking system: Evenly distributed load (sacks) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68 °F.