


D3
48" x 40"



Art.-Nr.: 83325240

Technical Data*1

Dimensions L x W x H 48 x 40 x 5.9" (1200 x 1000 x 150 mm)

Weight (lbs) 39.7 lbs

Material*2 PE

Load capacity (lbs)



Static
11000 lbs



Dynamic
3300 lbs



In Racking System
2800 lbs


Characteristics

Color: black
Runners: 3, unwelded
Reinforcement profiles: 4
Temperature stability: -22°F to +104°F, briefly up to +194°F

Options


Transponder (RFID)
Reinforcement profiles
Lip options
Antislip
Lid

Loading quantities (Pcs / Approximate amount)

| | | | |
|---|------------------|--|--|
|  Truck | Container | Container 20': 140 Container 40': 330 | Container 40' High Cube: 365 Conventional trailer 45' high cube container: - |
| | | MEGA-Trailer: 494 | Jumbo: 532-570 |

Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data reflect characteristic features tested under specially defined conditions. Variations may occur due to different usage conditions, such as loading method, ambient temperature, and storage duration. All data and specifications are subject to change without notice. Our service team is happy to assist in reviewing the specific requirements of your individual application.

*2 Our service team is available to provide precise information about material compositions.

*3 **Static load:** Resistance to pressure on a flat surface with an evenly distributed load at a room temperature of approx. 68°F.

Dynamic load: On a forklift with an evenly distributed load at a room temperature of approx. 68°F.

In racking system: Evenly distributed load (sacks) along the longitudinal sides, resting on two supports for over 100 h at a room temperature of approx. 68°F.