










SL1

47.2" x 31.5"



Art.-Nr.: 83259801

Technical Data*1				
Dimensions L x W x H		47.2 x 31.5 x 4.7 " (1200 x 800 x 120 mm)		
Weight(lbs)		15.4 lbs		
Material*2		PE		
Load capacity (lbs)		<div> Static 4450 lbs</div>	<div> Dynamic 2200 lbs</div>	<div> In Racking System</div>
Characteristics		Options		
Color: basalt gray		Lip options		
Runners: 3, unwelded		Lid		
Lips: 0.3 "				
Temperature stability: -22°F to +104°F, briefly up to +194°F				
Loading quantities (Pcs / Approximate amount)				
<div> Container</div>	Container 20': 248 Container 40': 504	Container 40' High Cube: 558 Conventional trailer 45' high cube container: -		
<div> Truck</div>	MEGA-Trailer: 816	Jumbo: 912		
Labelling				
Customized printing and numbering available on request depending on quantity. Position upon consultation.				



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68°F.
Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68°F.
In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68°F.