







CB1 UN 4H2

4H2/Y438/S/./D/BAM 15814-CR



Art.-Nr.: 83381819

Technical Data*1

| | | | |
|---------------------|---|--|---|
| External Dimensions | 47.2 x 31.5 x 29.1" (with lid: 48.7 x 32.9 x 30.1") | Internal Dimensions | 43.9 x 28.1 x 23.4" |
| Weight (lbs) | 87.7 lbs | Volume | 125 gal |
| Material*2 | PE | | |
| Load capacity (lbs) |  Extra Load 1406kg |  Holding Capacity 1000 lbs |  Dynamic Load |

Characteristics

Color: light gray
 Manufactured in one piece
 Runners: 3, unwelded
 With lid and 2 tensioning straps
 Stackable
 Temperature stability: -22°F to +104°F, briefly up to +194°F
 Resistant to most chemicals and cleaning agents
 Food-safe. HACCP compliant
 Container is based on DIN EN 13626 and DIN EN ISO 12048
 The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)

Options


Transponder (RFID)

Loading quantities (Pcs / Approximate amount)

| | | |
|---|--|---|
|  Container | Container 20': 31 Container 40': - | Container 40' High Cube: 72 Conventional trailer 45' high cube container: - |
|  Truck | MEGA-Trailer: 95 | Jumbo: 110 |

Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
 *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.