




SB 265 gal UN 4H2 4H2/Y474/S/../D/BAM 16337-CTP



Art.-Nr.: 81941997

| Technical Data*1 | | | |
|------------------------|--|---------------------------|----------------------|
| External Dimensions | 63.0 x 47.2 x 31.1 " (with lid: 63.7 x 48.0 x 33.9 ") | Internal Dimensions | 59.8 × 44.1 × 23.2 " |
| Weight(lbs) | 162.1 lbs | Volume (I) | 265 gal |
| Material* ² | PE | | |
| Load capacity (lbs) | Stacking Load 2800 lbs | Holding Capacity 1000 lbs | → kg Dynamic Load |

Characteristics **Options**

Color: light gray Runners: 4, unwelded

Temperature stability: -22°F to +104°F, briefly up to +194°F

Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048


The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)

Loading quantities (Pcs / Approximate amount)

On request

Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.







Transponder (RFID)



- All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.