




CR147.2" × 31.5"




Art.-Nr.: 83230891


Technical Data*1			
Dime nsions L x W x H	47.2 x 31.5 x 6.3" (1200 x 800 x 160 mm	1)	
Weight(lbs)	41.9 lbs		
Material* ²	PE		
Load capacity (lbs)	Static 16540 lbs		Racking System 860 lbs
Characteristics		Options	
Color: dark gray/blue Runners: 3, unwelded Transponder: Yes Reinforcement profiles: 3 Antislip: Palgrip® anti-slip strips on the top deck		Lip options Lid	
Temperature stability: -22°F to +104°F, briefly up to +194°F			
Loading quantities (Pcs / Approximate amo	ount)		
Container	Container 20': 192 Container 40': 390	Container 40' High Cube: 440 Conventional trailer 45' high cube cont	ainer:-
Truck	MEGA-Trailer: 612	Jumbo: 684	

Labelling

Customized printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68° F.
 Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68° F.
 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68° F.