










D3 ECO

1200 x 1000 mm



Art. no. 83325201

Technical data *1			
Dimensions L x W x H (mm)	1200 x 1000 x 150		
Weight (kg)	14.0		
Material*3	HDPE, Regranulated material		
Load capacity (kg)*2	 Static 5000	 Dynamic 1000	 In racking system 400
Characteristics		Options	
Colour: black Runners: 3, unwelded Rims: 7 mm Temperatur stability: -30°C to +40°C, briefly up to +90°C Manufactured from regranulated material of one single type		Transponder Reinforcement profiles Rims Antislip	
Loading quantities (pcs/approx.)			
 Container	Container 20': 140 Container 40': 330	Container 40' High Cube: 374 Conventional trailer 45' high cube container: 416	
 Truck	MEGA-Trailer: 494	Jumbo: 570	
Labelling options			
Customised printing and numbering available on request depending on quantity. Position upon consultation.			



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.

*3 Although still within ISO compulsory range, the load-bearing test results using pallets made from regranulated material show slightly more variation than those from virgin HDPE.