





CR4-5

48 x 40 inches

Palgrip



Please note: Drawing shows version without lips

Art. no. 83350301

Technical data ^{*1}

Dimensions in inches (L x W x H)^{*2} 48 x 40 x 5.9 (1219 x 1016 x 150 mm)

Weight in lbs^{*2} 52 (in kg: 23.5)

Material^{*3} PE

Load capacity in lbs^{*4}



Static
16500 (in kg: 7500)



Dynamic
2750 (in kg: 1250)



In racking system
2200 (in kg: 1000)

Characteristics

Colour: light blue / blue

Runners: 5, unwelded

Lips (height in inches): 0.2 (in mm: 5.0)

Antislip: Yes, 5 Palgrip® antislip strips on the top deck

Temperature stability (in F): -22° to +104°, briefly up to +194°

Loading quantities (pcs/approx.)




Container

40' High Cube: 358

Dry Van: 448

Labelling options

Customized printing and numbering available on request depending on quantity. Ask about label position options.



^{*1} All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

^{*2} All measurements and weight indications are conversion values derived from the original metric values. The possible range of tolerance can be found in the technical drawing. All tolerances are within the accepted tolerance range as specified in the respective DIN norm. If you require more information on our tolerances please contact our sales team.

^{*3} Our service team is pleased to be at your disposal if you require exact information about material compositions.

^{*4} Load capacity indications are conversion values derived from original metric values. Minor rounding differences are possible.

Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 68 °F (20 °C).

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 68 °F (20 °C).

In racking system: evenly distributed load along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 68 °F (20 °C).