



D1

1200 x 800 mm



Art. no. 83360700



Technical data ^{*1}

Dimensions L x W x H (mm)	1200 x 800 x 150		
Weight (kg)	12.0		
Material ^{*2}	HDPE, Virgin material		
Load capacity (kg) ^{*3}	 Static 5000	 Dynamic 1000	 In racking system 400



Characteristics

Colour: redbrown
 Runners: 3, unwelded
 Temperature stability: -30 °C to +40 °C, briefly up to +90 °C

Options


Transponder
 Reinforcement profiles
 Rim options
 Antislip

Loading quantities (pcs/approx.)

	Container	Container 20': 215 Container 40': 440	Container 40' High Cube: 490 Conventional trailer 45' high cube container: 544
		Truck	MEGA-Trailer: 646 Jumbo: 684-722

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.



^{*1} All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

^{*2} Our service team is pleased to be at your disposal if you require exact information about material compositions.

^{*3} **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.