









TC3-5

1200 x 1000 mm



Art. no. 87030840

| Technical data ^{*1} | | | |
|---|---|--|--|
| Dimensions L x W x H (mm) | 1200 x 1000 x 160 | | |
| Weight (kg) | 22.5 | | |
| Material ^{*2} | HDPE, Virgin material | | |
| Load capacity (kg) ^{*3} |  Static 7500 |  Dynamic 1500 |  In racking system 1250 |
| Characteristics | | Options | |
| Colour: light grey Runners: 5, unwelded Rims: 7 mm Temperature stability: -30 °C to +40 °C, briefly up to +90 °C | | Transponder Reinforcement profiles Rim options | |
| Loading quantities (pcs/approx.) | | | |
|  Container | Container 20': 141 Container 40': 300 | Container 40' High Cube: 340 Conventional trailer 45' high cube container: 390 | |
|  Truck | MEGA-Trailer: 468 | Jumbo: 504-540 | |
| Labelling options | | | |
| Customised printing and numbering available on request depending on quantity. Position upon consultation. | | | |



^{*1} All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

^{*2} Our service team is pleased to be at your disposal if you require exact information about material compositions.

^{*3} **Static load:** resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.

Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.

In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.